

NOTE:

1 ELECTRICAL CHARACTERISTICS:

1.1 FREQUENCY RANGE:DC~6GHz

1.2 IMPEDANCE:75Ω

1.3 VSWR:1.5 MAX @ 6GHz.

1.4 INSULATION RESISTANCE: 5000MΩ MIN.

1.5 CONTACT RESISTANCE

1.5.1 CENTER CONTACT: 3 MΩ

1.5.2 OUTER CONTACT: 2.5 MΩ


2 MECHANICAL CHARACTERISTICS:

2.1 TEMPERATURE RANGE: -65°C~+165°C


2.2 DURABILITY: 500 CYCLES.

3 ALL MATERIALS AND PROCESS ARE RoHS COMPLIANT

Rev.	ECN#	Description	Changed by	Date
A	NONE	FIRST RELEASE.	T.WANG	2019-04-10



RECOMMENDED STRIPPING DIMENSION



⑦	SPRING	PIANO WIRE	NICKEL	1 EA
⑥	GASKET	SILICONE RUBBER	NATURE	1 EA
⑤	FERRULE	BRASS	NICKEL	1 EA
④	CONTACT PIN	BRASS	GOLD	1 EA
③	INSULATOR	TEFLON	NATURE	1 EA
②	BODY	BRASS	NICKEL	1 EA
①	BAYONET SLEEVE	BRASS	NICKEL	1 EA
ITEM	NAME	MATERIAL	TREATMENT	QTY

Bill Of Material

TOLERANCES UNLESS OTHERWISE SPECIFIED		
ONE PLACE DECIMAL	.X	±0.20
TWO PLACE DECIMAL	.XX	±0.10
THREE PLACE DECIMAL	.XXX	±0.02
HOLE DIA. VARIATION	.XX	N/A
ANGULAR DIMENSION		±3°

Signature	
Approved By:	
Checked By:	
Drawn By:	

SHINTO SHINTO ELECTRONICS CO.,LTD http://www.shinto-electronics.com			
Shinto P/N:		BMS11G060-A335	
Description:		BNC plug S/T for RG6 coaxial cable	
Material:		See BOM	Treatment: See BOM
Unit:	mm	Size: A4	Scale: 3:1
		Sheet: 1 of 1	